

Installation Instructions

WB49X20202 Café Gray Badge

Purpose

To provide instructions to replace the current red Café badge with a gray badge.

Use this part for the Café models specified below. Parts for other models can be ordered through the GE Parts department by calling 800-528-8684 .

Installation Procedure

Using a plastic pry tool, carefully pry away the current red badge from the product by starting on the right or left side at the 3'o'clock or 9'o'clock position. Many badges feature positioning pins and these are typically located at the 12, 4 and 8 o'clock positions.



Do not use any tool other than a plastic pry tool as other tools may scratch the stainless steel surface of the product.

Once the badge has been removed, use a plastic pry tool to gently scrape away any remaining adhesive.




Clean surface around old badge.

If needed, use rubbing alcohol or mineral spirits to clean and remove any surface oils or debris that may prevent proper adhesion of the new badge.

Test badge fit

Before removing the paper from adhesive backing, place the new badge directly over the area where the red badge was positioned. Check to be sure the new badge fits properly into the alignment holes (if applicable) and rests flat and evenly against the product. The new badge must fit flat to bond properly to the product.

Note: If the gray badge is damaged, or the size, or positioning pins are not a proper fit, call the GE Parts department at 800-528-8684 to order a new part. Make sure to have the model number of the product available.



Install the new badge

Peel off the paper from adhesive backing and carefully align the new badge directly over the area where the red badge was positioned.

Check to make certain the new badge is correctly aligned on all sides.

Once proper alignment is achieved, apply pressure evenly to the badge and hold against the product for at least 15 seconds. Press around the circumference of the new badge to ensure proper adhesive bond.

Check to ensure the badge fits flat, with no gaps and is securely seated against the product.

Note: If the new gray badge must be removed for any reason after the adhesive backing has bonded, a new gray badge should be ordered.

This part is for use on the following models:

Cooking	Dishwasher	Refrigeration
C2S985SET	CDWT980R	CFSP5RK
CS980SN	CDWT980V	CFCP1NIX
CS980ST	CDWT280V	CFCP1NIY
CGS990SET	CDW9380N	CFCP1NIZ
CGS985SET	CDW9380P	CFCP1RK
CS975SD		
C2S980SEM	Hoods	
CGS980SEM	CV936M	
CGS975SED	CV966T	
CT959ST		
CT918ST		